



Adhesive/Coatings
13271 Mt. Elliott Detroit, MI 48212 • (313) 893-4930 • Fax (313) 891-0014
ISO 9001:2008 Registered

CTI-4575 Aluminum Coating Marine Grade

CTI-4575 is used primarily on aluminum hulls for Pontoon Boats, House Boats and Fishing Boats.

Apply a thin film with a clean cloth after the aluminum hull has been cleaned and dried off.

Let dry for 24 hours.

- | | |
|----------------------------|-------------------|
| • Color | Clear |
| • Viscosity-Zahn cup#4 | 11.0 seconds |
| • UV resistance | excellent |
| • Adhesion | excellent |
| • Flexibility Mandrel bend | pass |
| • Flash Point | above 212°F |
| • Solids | 15-17% |
| • Humidity | 1000 hours – Pass |
| • Salt Spray | 1000 hours – Pass |

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED IS MADE regarding the performance or stability of any product, since the manner of use and conditions of storage and handling are beyond our control. Users of this information should make an independent determination of suitability and use of the product described, including evaluation of properties of product and precautionary measures in order to insure proper use of products described and the health and safety of all persons and property. No suggestions for product use, nor anything contained herein shall be construed as a recommendation of its use in infringement of any existing patent.