

PopPly 5.5TM

PopPly 5.5 is a five-ply, poplar plywood serving as an ideal underlayment for vinyl floor covering and carpet. Its unique five-ply construction, makes it indentation resistant, dimensionally stable, and non-staining. As with all wood products, correct storage, handling, and installation procedures are essential for a trouble-free installation.

PopPly Specifications

Material:

- Five-ply poplar plywood

Thickness:

- 5.5 mm (nominal)

Description:

- Solid core construction
- Clear sanded face - no defects
- Fully sanded and repaired back
- Exterior grade glue

Size:

- 4' x 4'
- 4' x 8'

Weight:

- Approximately 1,050 pounds per 4x4 skid (100 sheets)
- Approximately 2,100 pounds per 4x8 skid (100 sheets)

PATCHING & LEVELING:

Patch and level PopPly joints with a polymer modified cement based patch. Once the patch has dried completely, smooth and level by sanding.

FLOOR COVERING INSTALLATION:

Install floor covering according to the manufacturer's recommendations.

PopPly Features

- Ultrasonic testing to ensure quality assurance
- Processed in the USA
- Guaranteed not to warp, buckle, or delaminate after proper installation
- Meets flooring manufacturers specifications
- 10-Year Limited Warranty when used for Residential Installations
- Proprietary non-stain print pattern



Use Under:

**Vinyl
Floor Covering**

HALEX

For more information:
Halex Corporation
Phone (909) 622-3537
Fax (909) 622-3047
www.halexcorp.com