

# FOUNDATION

## CONTRACT CARPET CUSHION

Engineered for Double-Glue & Stretch-In Installations

# XP

### CUSHION ATTRIBUTES


<b>STYLE ▶</b>	FXP270 – 6' x 45' roll
<b>DESCRIPTION ▶</b>	FOUNDATION XP 0.250" gauge, 16 lbs. / ft. <sup>3</sup> density.
<b>MATERIAL ▶</b>	Frothed polyurethane – a visco-elastic “memory foam” material.
<b>THICKNESS ▶</b>	0.250"
<b>BOTTOM FABRIC ▶</b>	RELEASE releasable woven backing for ease of removal at the end of useful life.
<b>DURABILITY ▶</b>	Compression Set . . . . . 7% max. Indentation Load Deflection (25%) . . . . . 15.50 lbs. / ft. <sup>2</sup> Indentation Load Deflection (65%) . . . . . 80.00 lbs. / ft. <sup>2</sup>
<b>FIRE RATING ▶</b>	NBS Smoke Chamber . . . . . <100 max. Pill Test (FF 1-70) . . . . . Pass
<b>SOUND RATING ▶</b>	Impact Insulation Class (ASTM E492-90) . . . . . 70 IIC
<b>INSULATION RATING ▶</b>	R-Factor (ASTM C 518) . . . . . 0.75 Excellent for radiant heated floors.
<b>WATER RESISTANCE ▶</b>	British Spill Test Method E . . . . . Pass Breathable Integral Skin Barrier, allows vapor to pass while blocking liquid spills, making clean-up easier and more effective.
<b>ROLL SPECIFICATIONS ▶</b>	6' x 45' roll, 270 sq. ft., 30 sq. yd. (98 lbs.)
<b>WARRANTY ▶</b>	Double-glue – Warranted term equal to that of co-installed carpet warranty. Stretch-in – Warranted for two carpet installations.

NOTE: Specification values subject to a 7% manufacturing tolerance.

### PRODUCT SPEC



6' X 45' ROLL



14"  
 ROLL DIAMETER  
 CORE SIZE: 3.625"

### GREEN PROPERTIES

<b>RENEWABLE CONTENT ▶</b>	Made in part with eco-friendly soybean oil, lessening dependence on petrochemicals. This reduces global warming emissions and the need for foreign oil while supporting local farmers and local producers <i>Applicable towards LEED Credit MR 6 – Rapidly Renewable Resources.</i>
<b>INDOOR AIR QUALITY ▶</b>	CRI Green Label certified. The only carpet cushion GREENGUARD Indoor Air Quality Certified® as a low emitting interior building material. <i>Applicable towards LEED Credit EQ 4.3 – Low Emitting Product.</i>
<b>ANTIMICROBIAL ▶</b>	Ultra-Fresh® Antimicrobial prevents mold, mildew and bacterial growth while controlling dust mites for life-long odor free installation.
<b>RECYCLABLE ▶</b>	Zero-Landfill Manufacturing waste, all materials are reused in products with recycled content. Post consumer recyclable, a valued commodity as recycled foam in the manufacturing of rebond padding.

